



GY412 305 dpi



Thermal Printer | GY Series

- **Liner Eliminator**
Environmentally Friendly
- **Operational Benefits**
Reduces Risk of Mismatched Packing Slips
- **Lower Cost**
Eliminates the Need for Additional Printers



Adding Another Dimension to Thermal Printing — SATO's Specialty Series of Printers —


A direct thermal printer that simultaneously prints on both sides of a label; the printer has 2 thermal print heads. The thermal label media is coated on both sides using thermal technology.

Industry Applications

- Transportation
- Logistics
- Shipping Labels
- Return Labels
- Packing Slips
- Invoices
- Customer Communications
- E-Commerce
- Financial

Combinations to Utilize Two-Sided Combinations

- Shipping + Return Label
- Shipping Label + Packer Slip
- Shipping Label + Invoice
- Shipping Label + Content Label/Packer Slip
- Shipping Label + Customer Communication or Marketing



www.satoamerica.com



GENERAL SPECIFICATIONS

GY412

MODEL		GY412
PRINT SPECIFICATIONS		
Print Method		Direct Thermal
Print Resolution		305 dpi (12 dots/mm)
Print Speed		Up to 10 ips (25 mm/sec)
Maximum Print Area		4.09" (104 mm) W x 11.8" (300 mm) L
MEDIA SPECIFICATIONS		
Sensor Type		Reflective Sensor (for use with pre-printed marks) See-Through Sensor (for die-cut labels with gap)
Media Type		Fanfold
Media Size	Width	1.97" (50 mm) - 5.16" (132 mm)
	Length	1.18" (30 mm) - 11.8" (300 mm)
	Thickness	0.004" - 0.013" (0.1 mm - 0.32 mm)
FONT/BARCODE SYMBOLOGIES		
Fonts		OCR-A, OCR-B, X20, X21, X22, X23, X24, CG Times, CG Triumvirate
Barcode	Elementary	UPC-A/E, UCC/EAN-128, Interleaved 2 of 5, CODE 39, CODE 128, EAN-8/13, CODE 93, RSS-14, POSTNET, NW-7, Matrix 2 of 5, MSI, Bookland
	2-D	Data Matrix, PDF417, Macro PDF, Maxicode, Micro PDF417, Composite Symbology, QR Code
Programming Language		SBPL
COMMUNICATION INTERFACE		
Interface Options		RS232C, USB (2.0), LAN (10/100BaseT)
MEMORY		
Memory		16 MB SDRAM, 16 MB Flash ROM, SD Card Slot
OPERATING CHARACTERISTICS		
Power Requirements		100 -120/200-240 Volts AC \pm 10%, 50/60 Hertz \pm 5%
Environment	Operating	41° - 104°F (5° - 40°C), 15 - 85% RH, non-condensing
	Storage	-4° - 140°F (-20° - 60°C), 15 - 85% RH, non-condensing
Dimensions		8.4" W (213 mm) x 11.9" D (303 mm) x 11.1" H (281 mm)
Weight		30 lbs (13.5 kg)
OPTIONAL FEATURES		
Label Cutter		


GREEN SOLUTIONS™



SATO AMERICA, INC.

CORPORATE
10350-A Nations Ford Rd
Charlotte, NC 28273
Phone: (704) 644-1650
Fax: (704) 644-1662
satosales@satoamerica.com

LABEL MANUFACTURING, SERVICE & SALES

NORTH AMERICA	BRAZIL	ARGENTINA
Illinois	Sao Paulo	Buenos Aires
Florida		
New Jersey		
North Carolina		

©2013 SATO America, Inc. All rights Reserved. Rev H • Specifications subject to change without notice • Any unauthorized reproduction of this content, in part or whole, is strictly prohibited • SATO is a registered trademark of SATO Corporation and its subsidiaries in Japan, the U.S. and other countries. All other trademarks are the property of their respective owners.