

Item # 3600PA, 3600PA Series Label Printer Applicator

3600PA Series Label Printer Applicator

The 3600PA Printer Applicator is a rugged and versatile, high speed, thermal transfer labeler used to print and apply pressure sensitive labels to various products. A Sato or Zebra print engine is integrated into an applicator to form a self-contained unit to print variable data.

Assembled with right or left hand Sato and Zebra printer modules, the unit can be mounted in various positions to apply labels to the tops, sides or bottoms of a multitude of products with its proven tamp-blow application.

Small and large labels up to 7.1" wide can be accommodated with its built-in bar codes and alpha-numeric fonts and 203, 305 or 600 dpi print resolution.

The plc control with user-friendly display interface offers quick access to set-up selection for application operating parameters. This feature can also be accessed by remote input.

Various onboard I/O signals are pre-wired to an external connector; optional features may be added in the field with minimum investment.

Label Size Range for the Sato is 1.0" wide x 1/4" long minimum to 6.5" wide x 10" long maximum, and for the Zebra is 1/2" wide x 1/2" long minimum to 7.1" wide x 10" long maximum.

NOTE: Sizes dependent upon print engine model, also contact CTM Integration for custom sizes or shapes.

Print Resolution and Speed are 203 dpi, 305 dpi and 600 dpi. with print speeds programmable up to 12"/sec, dpi dependent.


Print capabilities include fonts of various sizes and styles with independent height and width expansion; includes OCR A/B. Bar Codes include EAN 8/13, Code 39, Code93, UPC A/E (with extensions), Code 128, 2 of 5, Maxicode, DataMatrix, PDF417, MicroPDF, CODABAR, MSI, and POSTNET.

The Graphics feature supports user defined fonts and graphics including custom logos.

Labeling Speed is dependant upon label size, print speed and application type.

Standard Machine Features include Heavy Duty Construction, Tamp Blow Applicator, External Valves and Controls, Operator Keypad & Display, 12" O.D. Label Roll, I/O Connection and Communication Port Connections.

Optional features include Low Label/Low Ribbon, Out Of Label/Out of Ribbon, End of Web, Red, Amber and Green "Ready" Stack Lights and 16" Powered Unwind for large label rolls.



[· SPECIFICATIONS](#) · [· LABEL SIZES](#) · [· ENVIRONMENTAL](#)

SPECIFICATIONS

Series	3600PA
Length	31.5 in
Width	27.5 in
Height	23.5 in
Approx. Weight	150 lbs

Voltage	108-132 VAC
Current	5 amps
Frequency	50/60 Hz
Phase	Single
Pneumatic	90 psi 3-5 cfm
Communications	RS 232, Parallel Others available
Printing Methods	Thermal Transfer & Direct Thermal

LABEL SIZES

Min. Sato (W x L)	1.0 x 1/4 in
Max. Sato (W x L)	6.5 x 10 in
Min. Zebra (W x L)	1/2 x 1/2 in
Max. Zebra (W x L)	7.1 x 10 in

ENVIRONMENTAL

Environmental (Operating)	(5°C to 40°C) 41°F to 104°F
Environmental (Storage)	(-20°C to 40°C) -4°F to 104°F



3261 Commercial Parkway • Memphis, TN 38116
 Tel: (901) 332.6735 • Toll Free: 1-866-804-5291
 Fax: (901) 332.1834

E-mail: grdouglas@grdouglas.com
 Visit: grdouglas.com